

YES-EU EMERGENCY CHARGER

65 kWh to 322 kWh

Emergency Charger



65 kWh to 322 kWh



Available in a modular system with battery capacities ranging from 65 kWh to 322 kWh and charging power from 60 kW to 150 kW, featuring one or two separately integrated charging guns.

- ✓ Modular high-power charging system
- ✓ 60 kW - 150 kW charging power
- ✓ 65 kWh - 322 kWh battery capacity
- ✓ One or two charging cables
- ✓ OCPP 1.6 remote management

Technical Specification

Capacity range: 65 kWh - 322 kWh

Charging power: 60 kW - 150 kW

Maximum charging current: ≤ 250 A

Charging gun Output power: 150 kW

Gun Output current (A): 0-200 (CCS2); 0-250 (GB/T)

Gun Output voltage Range: 300 ~ 1000 Vdc

Charging Gun Standard: 1 or 2 x CCS2 connector, length 7 meters

Charging mode: Touch start, 10" touchscreen

OCPP support: OCPP 1.6 json

Operating temperature range: -10 °C - +60 °C

Storage temperature range: 0 °C - +45 °C

DC recharge: ≤ 250 A

AC recharge: 63 A (Industrial socket)

Protection level: IP54

Heat dissipation: Energy storage liquid cooling

Dimensions, mm (W, D, H): 2300 x 1500 x 1200 (175 kWh charger)

Weight ~ 1980 kg (175 kWh charger)

Active safety: Insulation detection, SOC, temperature, fire, voltage, emergency stop

